

OR □

DENOTES TERMINAL BLOCK

SUPER SYSTEMS INC.
(800) 666-4330
www.supersystems.com

1 - 24VDC (COM)	12 - RELAY OUT 5	22 - SLAVE 2 RS485 (+)
2 - 24VDC (+)	13 - RELAY OUT 6	23 - SLAVE 2 RS485 (-)
3 - RS485 RT (-)	14 - RELAY OUT 7	24 - 4-20mA OUT 1 (-)
4 - RS485 RT (+)	15 - RELAY OUT 8 NC	25 - 4-20mA OUT COM (+)
5 - SLAVE 1 RS485 (+)	16 - RELAY OUT 8 NO	26 - 4-20mA OUT 2 (+)
6 - SLAVE 1 RS485 (-)	17 - DIGITAL IN 1	27 - ANALOG IN 3 (+)
7 - RELAY COMMON	18 - ANALOG IN 2	28 - ANALOG IN 3 (+)
8 - RELAY OUT 1	19 - DIGITAL IN 3	29 - ANALOG IN 2 (+)
9 - RELAY OUT 2	20 - ANALOG IN 4	30 - ANALOG IN 2 (+)
10 - RELAY OUT 3	21 - DIGITAL IN COM	31 - ANALOG IN 1 (+)
11 - RELAY OUT 4		32 - ANALOG IN 1 (+)

SERIES 9215 PINDOUT LABEL

REFERENCE DRAWING(S)
THIS DRAWING IS FURNISHED AS A
GUIDELINE ONLY.
FINAL INSTALLATION DIAGRAMS
ARE THE RESPONSIBILITY OF OTHERS.
CONFIDENTIAL

REV. A	ECD - 00412	GDG	24 MAR 2017	DATE	APPROVED
DESCRIPTION	SERIES 9215 ATMOSPHERE AND TEMPERATURE CONTROL SYSTEM - RS-485 COMMUNICATIONS TO 5.7" DIT BASIC WIRING DIAGRAM				
ISSUED	DATE	ISSUED	SCALE	1:1	SHEET 01 OF 02
CHECKED	DATE	CHKD	ELECTRONICS\13594\		
DRAWN	GDG	26 FEB 2014	DATE	CHKD	
APPROVALS	DATE	DWG. NO.	13594	REV.	A

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES FRACTIONS DECIMALS ±1/64" ANGLES ±0.5° X, XX=±0.100 X, XXX=±0.001 SPECIFICATIONS HEREIN IS STRICTLY PROHIBITED OR USE OF THIS DRAWING OR THE INFORMATION AND CONTENTS HEREIN IS DAINED BY SUPER SYSTEMS, INC. (SSI). SSI RESERVES ALL RIGHTS INCLUDING TITLE, COPYRIGHT, PATENT RIGHTS AND THE RIGHT OF POSSESSION IN THE DRAWING AND ITS CONTENTS, EXCEPT AS AUTHORIZED BY SSI IN WRITING. ANY DISCLOSURE, REPRODUCTION, OR USE OF THIS DRAWING OR THE INFORMATION AND CONTENTS HEREIN IS STRICTLY PROHIBITED.



CINCINNATI, OHIO

